Storage container ISO standard steel containers, spacious and durable

ela[container]





Brief Description

Modern storage rooms have to meet a range of requirements. ELA storage containers are spacious and dry, ready for use in no time and deliver guaranteed durability even in the toughest deployment conditions.

Thanks to the fully-welded trapezoidal sheeting on the roof and walls, as well as the sturdy steel frame construction, the tools and materials are properly stored at all times.

Suitable equipment is provided for all purposes. In this way, ELA storage containers can optionally be delivered with shelving and complete electrical installation. For increased safety, they are enhanced with theft protection. Work benches, air-conditioning units and heaters are available as additional equipment options.

ELA storage containers feature a standard length of 20 feet, with a half-length version measuring 10 feet also available.

The ELA storage containers meet the high quality standards of ELA: Certified quality – Made in Germany.

Features

- + Sturdy steel frame construction made of 6 mm thick special profile
- + Heavy-duty double swing door
- + Roof, side walls and end walls made of 1.5 mm thick, fully welded trapezoidal sheeting
- + 8 ISO container corners
- + Plywood glued multiple times over the crosswise floor joists
- + ELA anti-theft system
- + Optional: heavy-duty shelving and electrical installation
- + Optional: Hook rail
- + Optional: Workbench with vice
- + Optional: Fire extinguisher
- + Optional: First-aid kit

10 foot ELA storage container

Article: CF10N25-M000

External dimensions: 2,991 mm × 2,438 mm × 2,591 mm

Internal dimensions: 2,831 mm x 2,352 mm x 2,390 mm (CRH)



Equipment

- + Heavy-duty double swing door
- + Sturdy steel frame construction made of 6 mm thick special profile
- + Roof, side walls and end walls made of 1.5 mm thick, fully welded trapezoidal sheeting
- + 8 ISO container corners
- + Plywood glued multiple times over the crosswise floor joists
- + ELA anti-theft system
- + Optional: Hook rail
- + Optional: Workbench with vice
- + Optional: Fire extinguisher
- + Optional: First-aid kit

20 foot ELA storage container

Article: CF20N25-M000

External dimensions: 6,058 mm × 2,438 mm × 2,591 mm

Internal dimensions: 5,898 mm x 2,352 mm x 2,390 mm (CRH)



Equipment

- + Heavy-duty double swing door
- + Sturdy steel frame construction made of 6 mm thick special profile
- + Roof, side walls and end walls made of 1.5 mm thick, fully welded trapezoidal sheeting
- + 8 ISO container corners
- + Heavy timber floor boards (wood flooring) over the crosswise floor joists
- + ELA anti-theft system
- + Optional: Hook rail
- + Optional: Workbench with vice
- + Optional: Fire extinguisher
- + Optional: First-aid kit

10 foot ELA storage container with shelves and electrical installation

Article: CF10N25-MREE External dimensions: 2,991 mm × 2,438 mm × 2,591 mm Internal dimensions: 2,831 mm x 2,352 mm x 2,390 mm (CRH)



Equipment

As CF10N25-M000, but with the following accessories:

- + Electrical installation 400/230 V, 50 Hz, IP44
- + Electric input and output CEE 400 V/32 A
- + Electric subdistribution board with ground fault circuit interrupter and various circuit breakers
- + Grounded receptacles and light switches
- + 1 surface-mounted light fixture, 29W
- + 1 CEE wall outlet 400 V/32 A
- + 1 Heavy-duty shelf on long side
- + ELA anti-theft system
- + Hook rail
- + Optional: Forced air heater, 2 kW

20 foot ELA storage container with shelves and electrical installation

Article: CF20N25-MREE External dimensions: 6,058 mm × 2,438 mm × 2,591 mm Internal dimensions: 5,898 mm x 2,352 mm x

Internal dimensions: 5,898 mm x 2,352 mm x 2,390 mm (CRH)



As CF20N25-M000, but with the following accessories:

- + Electrical installation 400/230 V, 50 Hz, IP44
- + Electric input and output CEE 400 V/32 A
- + Electric subdistribution board with ground fault circuit interrupter and various circuit breakers
- + Grounded receptacles and light switches
- + 2 surface-mounted light fixtures, each 29W
- + 1 CEE wall outlet 400 V/32 A
- + Heavy-duty shelving on long and short sides (L-shape)
- + ELA anti-theft system
- + Hook rail
- + Optional: Forced air heater, 2 kW

Equipment